

# T3AB132S-4 5,5KW 400/690V B14

## Three-phase asynchronous brake motor in aluminum

Motor type T3AB132S-4 5,5KW 400/690V B14  
 Brand BUSCK  
 Item number B3041323e

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	5,5	50	10,5	1460
690	5,5	50	6,04	1460
460	6,33	60	10,5	1752

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	89,6
Insulation class	F	Efficiency, load 75%	89,8
Cooling	IC411 (TEFC)	Efficiency, load 50%	89,4
Max. ambient temp.	40°C	Power fact, load 100%	0,84
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	59,05
Torque, Nm	35,98	Sound pressure Lp dB(A)	71
Starting torque ratio	2,3	Bearing DE	6308-2Z/C3
Pull up torque ratio	1,9	Bearing NDE	6208-2Z/C3
Pull out torque ratio	3,5	Balance grade	Normal
Starting current ratio	9	Inertia kgm <sup>2</sup>	0,03446419
		Cable entries	2xM25, 1xM16
Note	Brake motor IE3	Brake torque, Nm	80

