


T3AB90S-4 1,1KW 230/400V B5

Three-phase asynchronous brake motor in aluminum

Motor type T3AB90S-4 1,1KW 230/400V B5
 Brand BUSCK
 Item number B3040902e

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	1,1	50	4,43	1440
400	1,1	50	2,55	1440
460	1,27	60	2,55	1728

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	84,1
Insulation class	F	Efficiency, load 75%	84,1
Cooling	IC411 (TEFC)	Efficiency, load 50%	81,8
Max. ambient temp.	40°C	Power fact, load 100%	0,74
Min. ambient temp.	-20°C	Painting	Standard
Max. temp. rise	80 K	Color	RAL 9005
Max altitude, masl	1000	Weight kg	18,48
Torque, Nm	7,3	Sound pressure Lp dB(A)	61
Starting torque ratio	3,7	Bearing DE	6205-2Z/C3
Pull up torque ratio	3,1	Bearing NDE	6205-2Z/C3
Pull out torque ratio	3,8	Balance grade	Normal
Starting current ratio	7,7	Inertia kgm ²	0,003841812
Note	Brake motor IE3	Cable entries	1xM20
		Brake torque, Nm	16



BUSCK
www.busck.eu

Busck & Co AB
 Gamla Riksvägen 14
 428 32 Göteborg
 Sweden
 556027-1990
info@busck.se

Busck & Co ApS
 Postboks 108
 0900 København C
 Denmark
info@busck.eu

Busck AS
 Skibåsen 35C
 4636 Kristiansand
 Norway
info@busck.no