

T3AB63A-4 0,12KW 230/400V B14

Three-phase asynchronous brake motor in aluminum

Motor type T3AB63A-4 0,12KW 230/400V B14
 Brand BUSCK
 Item number B3040633e

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	0,12	50	0,66	1360
400	0,12	50	0,38	1360
460	0,14	60	0,38	1632

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	64,8
Insulation class	F	Efficiency, load 75%	63,7
Cooling	IC411 (TEFC)	Efficiency, load 50%	57,6
Max. ambient temp.	40°C	Power fact, load 100%	0,70
Min. ambient temp.	-20°C	Painting	Standard
Max. temp. rise	80 K	Color	RAL 9005
Max altitude, masl	1000	Weight kg	4,93
Torque, Nm	0,84	Sound pressure Lp dB(A)	52
Starting torque ratio	2,2	Bearing DE	6201 2RZ C3
Pull up torque ratio	2	Bearing NDE	6201 2RZ C3
Pull out torque ratio	2,3	Balance grade	Normal
Starting current ratio	3,5	Inertia kgm2	0,000305
Note	Brake motor IE3	Brake torque, Nm	4

