

# T2A71B-4 0,37KW 230/400V B14 ATEX ZON 2/22


## Three-phase asynchronous motor in aluminum

Motor type T2A71B-4 0,37KW 230/400V B14 ATEX ZON 2/22  
 Brand BUSCK  
 Item number Q3040723e

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	0,37	50	1,76	1400
400	0,37	50	1,01	1400
460	0,43	60	1,01	1680

Duty	S1	Efficiency class	IE2
Enclosure	IP65	Efficiency, load 100%	72,7
Insulation class	F	Efficiency, load 75%	73
Cooling	IC411 (TEFC)	Efficiency, load 50%	69,2
Max. ambient temp.	40°C	Power fact, load 100%	0,73
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	6,3
Torque, Nm	2,52	Sound pressure Lp dB(A)	55
Starting torque ratio	2,4	Bearing DE	6204-2Z/C3
Pull up torque ratio	2	Bearing NDE	6204-2Z/C3
Pull out torque ratio	2,5	Balance grade	Normal
Starting current ratio	4,7	Inertia kgm <sup>2</sup>	0,00082
Winding protection	Thermistors	Cable entries	1xM20

Note ATEX II 3 D Ex tc IIIC T125°C Dc ZONE 22  
 ATEX II 3 G Ex nA IIC T4 Gc ZONE 2  
 IP65, Termistorer



**BUSCK**  
 www.busck.eu

Busck & Co AB  
 Gamla Riksvägen 14  
 428 32 Göteborg  
 Sweden  
 556027-1990  
 info@busck.se

Busck & Co ApS  
 Postboks 108  
 0900 København C  
 Denmark  
 info@busck.eu

Busck AS  
 Skibåsen 35C  
 4636 Kristiansand  
 Norway  
 info@busck.no