

T4A80A-4 0,55KW 230/400V B14

Three-phase asynchronous motor in aluminum

Motor type T4A80A-4 0,55KW 230/400V B14
 Brand BUSCK
 Item number 43040803

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	0,55	50	2,45	1440
400	0,55	50	1,41	1440
460	0,63	60	1,41	1728

Duty	S1	Efficiency class	IE4
Enclosure	IP55	Efficiency, load 100%	83,9
Insulation class	F	Efficiency, load 75%	83,3
Cooling	IC411 (TEFC)	Efficiency, load 50%	80,6
Max. ambient temp.	40°C	Power fact, load 100%	0,67
Min. ambient temp.	-20°C	Painting	Standard
Max. temp. rise	80 K	Color	RAL 9005
Max altitude, masl	1000	Weight kg	11
Torque, Nm	3,8003	Sound pressure Lp dB(A)	57
Starting torque ratio	3,4	Bearing DE	6204-2Z/C3
Pull up torque ratio	3,0	Bearing NDE	6204-2Z/C3
Pull out torque ratio	3,7	Balance grade	Normal
Starting current ratio	6,8	Inertia kgm ²	0,002047
		Cable entries	1xM20

Note Termokontakt
IE4

